





Wall Lights | 0 x powerLED 0 W DC 630 mA | CRI 80
86562M00



□70

52





Technical data

Type	Encasement with flange
Installation position	Wall lights
Installation environment	Outdoor
Light Source	LED
Optics	General Lighting
Current intensity	630mA
CCT / Tone	2700 K
Colour rendering index	80 Ra
C.C. / C.V.	CC
Safety class	3
IP	IP65
IK	IK10
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Operating temperature	-20 / +50
Driver included	No
Dimmable article	DALI - 1-10V
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	1 m
Resin potting	Yes
Type of light emission	Single emission
Net weight	0.190 Kg
Electrostatic discharge protection	No
Surge protection	No
Ordinary temperature on the glass	40 °C

Finishing casing

Material	Aluminium
Colour	grey RAL 9006
Processing	Open pore anodizing + Powder Coating

Electronics





Wall Lights | 0 x powerLED 0 W DC 630 mA | CRI 80
86562M00

Single emission wall lights for outdoor application. The super warm LED light source with a general lighting light distribution is composed of 0 powered LED with CCT of 2700 K and a CRI 80.

The device body is made of aluminium and features a grey ral 9006 finish, processed by means of open pore anodizing + powder coating. The ingress protection degree is IP65; the total weight is of 0.190 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 0,0 W. The power supply cable is included and features a 1 m length.

The device features protection class III and can be wall lights-mounted, with a 52 mm diameter hole (in plasterboard) with an outer casing, code 84338(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.

Illuminotechnical Features

Colour temperature	2700 K
Standard Deviation of Colour Matching	1/16 ANSI BIN
Colour rendering index	80 Ra

LED Life / Failure Ratio

L70 B10 C0 361980h (at Tj 60 Ta 25)



Quara_Q | Wall Lights | Accessories
86562M00



Outer casing

Type of installation: masonry L=72mm, H=62mm, D=62mm

Code

84338