



Pendant Luminaires | 198-264 V | 80 topLED 20 W DC - 22 W AC | CRI 90 | Base  
CA055DGBWDD

Double emission pendant luminaires for indoor application. The warm white LED light source with a double diffused light distribution is composed of 80 topLED LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 2645 lm, with a 132.3 lm/W nominal luminous efficacy.

The device body is made of aluminium and features a text green blue ral 6004 finish, processed by means of coating; the diffuser is made of aluminium with a coating treatment. The ingress protection degree is IP20;

The total absorbed power is 22 W The power supply cable is included and features a 2 m length.


The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

|                                        |                |
|----------------------------------------|----------------|
| Light Output Ratio (LOR)               | 66 %           |
| Source lumens                          | 2645 lm        |
| Delivered lumens                       | 1754 lm        |
| Consumption                            | 22 W           |
| Luminaire efficacy                     | 79 lm/W        |
| Colour temperature                     | 3000 K         |
| Standard Deviation of Colour Matching  | 3 Step MacAdam |
| Colour rendering index                 | 90 Ra          |
| Standard Operating Ambient Temperature | -20 / +50°C    |


|                                      |  |
|--------------------------------------|--|
| LED Life / Failure Ratio             |  |
| L70 B20 C0 72500h (at Tj 115 Ta 25 ) |  |

Delfi\_P | Pendant Luminaires | Accessories  
CA055DGBWDD



Dimmer - Phase cut (Max 100W) - Essential for dimming the lamp  
220-240V

Code  
KIT0026



Dimmer - Phase cut CASAMBI - Essential for dimming the lamp with Casambi  
Radio-frequenza, 85-240V

Code  
KIT0080