

Pendant Luminaires | 198-264 V | 112 topLED 32 W DC - 35 W AC | CRI 90 | Base
CA056DWHWDD

Double emission pendant luminaires for indoor application. The warm white LED light source with a double diffused light distribution is composed of 112 topLEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 4097 lm, with a 128.0 lm/W nominal luminous efficacy.

The device body is made of aluminium and features a text white ral 9003 finish, processed by means of coating; the diffuser is made of aluminium with a coating treatment. The ingress protection degree is IP20;

The total absorbed power is 35 W The power supply cable is included and features a 2 m length.

The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Energy efficiency class

This product contains a light source of energy efficiency class F.

Illuminotechnical Features

Light Output Ratio (LOR)	70 %
Source lumens	4097 lm
Delivered lumens	2902 lm
Consumption	35 W
Luminaire efficacy	82 lm/W
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra
Standard Operating Ambient Temperature	-20 / +50°C

LED Life / Failure Ratio

L70 B20 C0 72500h (at Tj 115 Ta 25)

Delfi_P | Pendant Luminaires | Accessories
CA056DWHWDD



Dimmer - Phase cut (Max 100W) - Essential for dimming the lamp
220-240V

Code
KIT0026



Dimmer - Phase cut CASAMBI - Essential for dimming the lamp with Casambi
Radio-frequenza, 85-240V

Code
KIT0080