



DODOT FADOD

Design by Simone Micheli

Ceiling or wall lamp with metal frame in aluminum and steel. The lighting source can be adjusted. Built-in dimmable LED source.

Typology: WALL / CEILING LAMP

Ratings

- •Built in ED module
- •Supply voltage: 220-240Vac
- •CCT 2700 or 3000K*
- •IP20
- Adjustable
- Surface installation over holes
- •Switch mode: on-off
- •Dimmable
- •Aluminum body painted
- •Closing optic







OPTIC-LENS 48°

Type

FΑ

OPTIC-REFLECTOR 35°


BC white

BL blue

NE black

OPTIC-REFLECTOR 15°

DODOT / DRIVER INCLUDED weight 0,9 Kg



volume 0,02 m³





Article Colours

DOD9 30

Beam - degrees Source

LED 17.5W - 3000K* 48°

Туре	Article	Colours	Beam - degrees	Source

CG concrete green

MD mauve dust

FA	DOD9 27	BC white	48°	LED 17.5W - 2700K
		BL blue		
		NE black		
		CG concrete green		
		MD mauve dust		



IP20 CRI≥90 220-240VAc 110 ~2000 lm* 114 lm/W*




example composition code FA DOD9 30 NE 48 LED

Compatibile con sistema Casambi su richiesta / Compatibility with Casambi system on request



weight 0,9 Kg volume 0,02 m³





DODOT / DRIVER INCLUDED

5050.	/ DIGIVER INCEDE	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		
Туре	Article	Colours	Beam - degrees	Source
FA	DOD9 30	BC white	35°	LED 17.5W - 3000K*
		BL blue		
		NE black		
		CG concrete green		
		MD mauve dust		

Туре	Article	Colours	Beam - degrees	Source
FA	DOD9 27	BC white	35°	LED 17.5W - 2700K
		BL blue		
		NE black		
		CG concrete green		
		MD mauve dust		

(€ ⊕ - | P20 CRI≥90 220-240Vac | ~2000 lm* 114 lm/W*

example composition code FA DOD9 30 NE 35 LED

Compatibile con sistema Casambi su richiesta / Compatibility with Casambi system on request

DODOT / DRIVER INCLUDED

Туре	Article	Colours	Beam - degrees	Source
FA	DOD9 30	BC white	15°	LED 17.5W - 3000K*
		BL blue		
		NE black		
		CG concrete green		
		MD mauve dust		

Туре	Article	Colours	Beam - degrees	Source
FA	DOD9 27	BC white	15°	LED 17.5W - 2700K
		BL blue		
		NE black		
		CG concrete green		
		MD mauve dust		

C € ⊕ → IP20 CRI ≥ 90 220-240Vac ► 2000 lm* 114 lm/W* example composition code FA DOD9 30 NE 15 LED

Compatibile con sistema Casambi su richiesta / Compatibility with Casambi system on request

DODOT – FADOD – technical sheet



Ava	ailable colours				
	White	Blue	Black	Concrete	Mauve dust
EEL	Lc (Energy Effi	ciency Label co	ompatibility) contain	n built in LED lam	ps that cannot b
FAI	DOD930 4	8 LED			
	DOD930 4		CUSTOMER		NOTES
FAI		8 LED			
FAI	DOD927 4	8 LED 5 LED			
FAI FAI	DOD927 4 DOD930 3	8 LED 5 LED 5 LED			
FAI FAI FAI	DOD927 4 DOD930 3 DOD927 3	8 LED 5 LED 5 LED 5 LED			

NOTICE: Luminous flux (lm) and efficacy (lm/W) for all built in LED luminaires is based on nominal ratings of the LED sources. Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.