MUSE – UP MUSE 80 E26 – technical sheet





UPMUSE80 E26


Design by Sandro Santantonio


Collection consisting of ceiling or wall lamps, suspended lamps and table lamps with metal frame and removable, washable elastic fabric covering. Available in several colours and sizes. Screw fitting light source.

Typology: WALL, CEILING LAMP

Ratings

- •E26
- Diffused light
- Surface installation over holes
- •Power supply 120V AC
- •Switch mode: on-off
- •Steel frame, painted





Ø 80 cm

Product code composition

MUSE / application: both as ceiling or wall lamp

Туре	Article	Colours	Finish	Source	•
UP	MUSE 80	BC white	XX white metal	E26	3 x Max 10W LED or 3 x Max 15W fluo
		AR* orange			
		GI* yellow			
		MC multicolour			
		FI flower			
		ST sticks			





DRY LOCATION

example composition code | UP | MUSE80 | GI | XX | E26

Silk stretch fabric

Comp. 84% polyester, 16% elastane (Spandex) for multicolour MC. Comp. 80% polyamide, 20% elastane (Spandex) for other colours.

Weight 170/190 gr/m² for multicolour MC. Weight 195/215 gr/m² for white BC. Weight 180/200 gr/m² for other colours.

Light fastness (ISO 105 B02) from 3 to 6 Glow wire 750°C for multicolour MC Glow wire 850°C for white BC / other colours.

Available colours



BC





GΙ Yellow



MC Multi



FΙ Flower



ST Sticks

*Upon request

CUSTOMER_

NOTES

UPMUSE80_ _XXE26

Luminous flux for all LED luminaires is shown at source level.

Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.