


Designed by Edward Barber and Jay Osgerby, 2018

2.5W - 151lm - 2700K

Rechargeable direct light table lighting device. Base and dome in coloured PC. Diffuser in Opaline injection moulded photo-engraved PC. 24-hours' autonomy, charging via Micro-USB-C. Push-button switch positioned on the base provides the 4-step dimmer function. Battery status indicator positioned under the base. USB-C charging cable included, useful length 120cm.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8059607001288
Mounting	Table
Enviroment	Indoor dry location
Light source type	LED
LED type	LED Module
Power (W)	2.5
System flux (lm)	151

Physical

Colour	Grey Blue
Length (mm)	210
Net weight (kg)	1.3
Package volume (m3)	0.01
IP internal	20

Download

Mounting instructions PDF

Spare Parts  PDF


Photometric Files

LDT / IES  LDT

Technical Drawings

2D ZIP3D  ZIP

Schematic light drawing



Photometric


Lighting type	Direct
Light distribution	Roto symmetric
CCT (K)	2700

Electrical


Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	100-240/5
LED voltage Vf (Vdc)	null
Driver	Remote excluded
Dimmable	Yes
Dimming type	Electronic 5V
Dimming interface	Dimmer Integrated
Batteries inside	Yes
Battery type	LI-PO
Charging max power	14
Charging min time	3h - 0% to 100%
Charging socket/connector	USB-C

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class C



Replaceable (LED only) light source by a professional



Replaceable control gear by an end-user

Spare Parts



RF1035109

Power charger with electrical
cable & plugs