

# FLOS

 F1060075 Brick Red

## Bellhop Table

Designed by Edward Barber and Jay Osgerby, 2018




2.5W - 151lm - 2700K

Rechargeable direct light table lighting device. Base and dome in coloured PC. Diffuser in Opaline injection moulded photo-engraved PC. 24-hours' autonomy, charging via Micro-USB-C. Push-button switch positioned on the base provides the 4-step dimmer function. Battery status indicator positioned under the base. USB-C charging cable included, useful length 120cm.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

|                   |                     |
|-------------------|---------------------|
| EAN               | 8059607001325       |
| Mounting          | Table               |
| Environment       | Indoor dry location |
| Light source type | LED                 |
| LED type          | LED Module          |
| Power (W)         | 2.5                 |
| System flux (lm)  | 151                 |

### Physical

|                     |           |
|---------------------|-----------|
| Colour              | Brick Red |
| Length (mm)         | 210       |
| Net weight (kg)     | 1.3       |
| Package height (cm) | 200       |
| Package width (cm)  | 200       |
| Package length (cm) | 330       |
| Package volume (m3) | 0.01      |
| IP internal         | 20        |

### Download

[Mounting instructions](#)  PDF

[Spare Parts](#)  PDF

### Photometric Files

[LDT / IES](#)  LDT


### Technical Drawings

[2D](#)  ZIP

[3D](#)  ZIP



## Schematic light drawing



## Photometric

|                    |                |
|--------------------|----------------|
| Lighting type      | Direct         |
| Light distribution | Roto symmetric |
| CCT (K)            | 2700           |

## Electrical


|                           |                   |
|---------------------------|-------------------|
| Insulation class          | III               |
| Frequency (Hz)            | 50/60             |
| Main voltage (Vac)        | 100-240/5         |
| LED voltage Vf (Vdc)      | null              |
| Driver                    | Remote excluded   |
| Dimmable                  | Yes               |
| Dimming type              | Electronic 5V     |
| Dimming interface         | Dimmer Integrated |
| Batteries inside          | Yes               |
| Battery type              | LI-PO             |
| Charging max power        | 14                |
| Charging min time         | 3h - 0% to 100%   |
| Charging socket/connector | USB-C             |

## Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class **C**



Replaceable (LED only)  
light source by a  
professional



Replaceable control  
gear by an end-user

## Spare Parts



RF1035109

Power charger with electrical  
cable & plugs