



F1530030 Anthracite/Black Marble

Captain Flint

Designed by Michael Anastassiades, 2015

20W - 554lm - 2700K

Floor lamp providing adjustable direct light. Painted steel or brushed brass, stem and metal spinning cone. Opal photoengraved PC diffuser by injection molding. White Carrara or Black Marquina marble base. Power cord length 260 cm, with foot dimmer switch that provide ON-OFF functions and 10-100% light adjustment. Plugin power supply with interchangeable plugs

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

| EAN | 8059607001431 |
|-------------------|---------------------|
| Mounting | Floor |
| Enviroment | Indoor dry location |
| Light source type | LED |
| LED type | LED array |
| Lamp holder | COB LED |
| Power (W) | 20 |
| System flux (lm) | 554 |

Physical

| Colour | Anthracite/Black Marble |
|---------------------|----------------------------|
| Cord length (mm) | 2600 |
| Net weight (kg) | 8.2 |
| Package volume (m3) | 0.22 |
| IP internal | 20 |



373 mm

Download

| Mounting instructions | 业 PDF |
|-----------------------|--------------|
| Mounting instructions | 业 PDF |
| Spare Parts | 业 PDF |

Photometric Files

LDT / IES

₹ LDT

Technical Drawings

| 2D | $\overline{\mathbf{A}}$ | ZIP |
|----|-------------------------|-----|
| 3D | <u></u> | ZIP |


















https://professional.flos.com/en/global/product/captain-flint-f1530030/

F1530030

Schematic light drawing



Photometric

| Lighting type | Direct |
|--------------------|----------------|
| Light distribution | Roto symmetric |
| CCT (K) | 2700 |

Electrical

| Insulation class | III |
|--------------------|---------------------------|
| Frequency (Hz) | 50/60 |
| Main voltage (Vac) | 100-240/48 |
| Driver | Remote included |
| Dimmable | Yes |
| Dimming type | Electronic 48V |
| Dimming interface | Dimmer Integrated |
| Plug type | Type G, Type A, Type C |
| Batteries inside | No |
| Charging min time | No |

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D



Replaceable (LED only) light source by a professional



Replaceable control gear by an end-user

Spare Parts





Black marble base



DE1530100

Screws with allen key and feet pads



RF26382

Switch dimmer 400Ma



RF3320400

Black plug assembly kit & 48V driver