



F1801033 Argent

Coordinates Floor


Designed by Michael Anastassiades, 2020

53W - 3049.4lm - 2700K - CRI> 95

Coordinates Floor is a floor lamp with diffuse light composed of two vertical poles that can be oriented during installation, attached to a base with an anodized aluminium cover. Each element is made of extruded anodized aluminium with a champagne or argent finish and a diffuser in platinum optical silicone with an integrated LED strip (CRI 95). Usable power cable length 260 cm with pedal dimmer switch for ON/OFF and adjustable brightness 10–100%. Power supply attached to interchangeable plug.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

| EAN | 8059607039830 |
|-------------------|---------------------|
| Mounting | Floor |
| Environments | Indoor dry location |
| Light Source Type | LED |
| LED type | LED Module |
| Power (W) | 53 |
| System flux (lm) | 3049.4 |

Physical

| Colour | Argent |
|---------------------|--------|
| Length (mm) | 380 |
| Net weight (kg) | 9.2 |
| Package volume (m3) | 0.03 |
| IP internal | 20 |

Download

| Mounting instructions | ⊥ PDF |
|-----------------------|--------------|
| Mounting instructions | ⊥ PDF |
| Spare Parts | 业 PDF |

Photometric Files

| JLD | ⊥ ZIP |
|-----------|--------------|
| _DT / IES | .↓, LDT |

Technical Drawings

| recinited brawings | |
|--------------------|--------------|
| 3D | ⊥ ZIP |
| a Bim | ⊥ ZIP |



















https://professional.flos.com/en/global/product/coordinates-floor-f1801033/

F1801033

Photometric

| Lighting type | Indirect, Direct |
|--------------------|------------------|
| Light distribution | Asymmetric |
| CCT (K) | 2700 |
| CRI> | 95 |

Electrical

| Insulation class | III |
|----------------------|---------------------------|
| Frequency (Hz) | 50/60 |
| Main voltage (Vac) | 100-240/48 |
| LED voltage Vf (Vdc) | null |
| Driver | Remote included |
| Dimmable | Yes |
| Dimming type | Electronic 48V |
| Dimming interface | Dimmer Integrated |
| Plug type | Type G, Type A, Type C |
| Batteries inside | No |

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class **F**




Replaceable (LED only) light source by a professional



Replaceable control gear by an end-user

Spare Parts



- 04. Switch dimmer 48v pmw 500hz RF27549
- 05. Black plug assembly kit & 48V RF3320400 driver

DOWNLOAD





RF27549

Switch dimmer 48v pmw 500hz

RF3320400

Black plug assembly kit & 48V driver