



Easy Kap 80 Square Adjustable


Designed by FLOS Architectural, 2016



Recessed luminaire with main voltage source. Mounting frame not required.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Ceiling recessed
Enviroment	Indoor dry location
Light source type	Bulb
Lamp category	LED retrofit
Lamp type	PAR16
Lamp holder	GZ10
Ilcos	No
Number of heads	1
System power (W)	50

Physical

Colour	White
Trim	Yes
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	20
Transversal tilting (°)	20
Recessed depth (mm)	155
Net weight (kg)	0.12
IP internal	20
IP external	23

Download

Mounting instructions



Ecodesign and Energy Labelling



Replaceable (LED only) light source by an end-













GWT 850° IP

https://professional.flos.com/en/global/product/easy-kap-80-square-adjustable-03.4213.b1/

03.4213.B1

Photometric

Lighting type	Direct
Light distribution	Symmetric

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	230
LED current (mA)	-9
Emergency type	No

Notes

Not suitable for lens accessories.