FLOS

F4640019 Yellow

OK

Designed by Konstantin Grcic, 2014

18W - 1551lm - 2700K

Lamp providing direct light. Head in gloss varnished. Body in injection-stamped PA66+30%FV with cover in gloss varnished. Orientable head. The light fitting can be moved vertically by running the internal structure of the body on a steel cable tensioned between the ceiling and the floor (useful length 4000mm). Dimmable switch with Soft Touch technology. Adaptor on plug connector with interchangeable plugs.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8059607020128
Mounting	Suspension
Enviroment	Indoor dry location
Light source type	LED
LED type	LED Module
Lamp holder	LED Module
Power (W)	18
System flux (lm)	1551

Physical

Colour	Yellow
Cord length (mm)	4000
Net weight (kg)	2.9
Package height (cm)	140
Package width (cm)	340
Package length (cm)	390
Package volume (m3)	0.02
IP internal	20

Download

Mounting instructions	PDF
Mounting instructions	PDF
Spare Parts	PDF

Photometric Files

LDT / IES	LDT

Technical Drawings

2D	ZIP
3D	ZIP

RETILAP

IK	IP
04	20

©2022 Flos - P.IVA 00290820174 - 3/2/2023

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order t improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.

Schematic light drawing



Luminous flux luminaire
1551 lm

Beam Angle: 61°

h(m)	E(lx)	D(m)
1	1158	1.19
2	289	2.38
3	129	3.57
4	72	4.76
5	46	5.95

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



Replaceable (LED only) light source by a professional



Replaceable control gear by an end-user

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700

Electrical

Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	100-240/24
Driver	Remote included
Dimmable	Yes
Dimming type	Electronic 24V
Dimming interface	Dimmer Integrated
Plug type	Type G, Type A, Type C
Batteries inside	No
Charging min time	No

©2022 Flos - P.IVA 00290820174 - 3/2/2023

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order t improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.

Spare Parts

RF23023

Counterweight

RF28255

Yellow led head assembly

RF3320100

Black plug assembly kit & 24V driver

RF4640100

Anchor with hook

RF4640200

Steel cable 6mt.

RF4640300

Steel cable 6mt.

RF4640400

Internal lamp body assembly

RF23031

Yellow ceiling rose

©2022 Flos - P.IVA 00290820174 - 3/2/2023

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order t improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.

RF06850

non c'è - ANDRA' IN SOSTITUZIONE DEL CODICE 06850 NEI PROSSIMI AGGIORNAMENTI - LAMPADA "OK"

RF22997

Yellow extrusion

©2022 Flos - P.IVA 00290820174 - 3/2/2023

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order t improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.