


Box_W1 Mono Emission



Wall Lights | 220-240 V
108 topLED 40 W DC - 41 W AC | CRI 80
8776



Technical data	
Type	Wall Lights
Installation position	Wall lights
Installation environment	Indoor
Light Source	LED
Optics	Diffused
Light emission direction	upward
Nominal power	40 W DC
Total Power	41 W
Source lumens	4630 lm
Voltage	220 - 240 V AC
Frequency	60 - 50 Hz
CCT / Tone	3000 K
Colour rendering index	80 Ra
C.C. / C.V.	AC
Safety class	1
IP	IP40
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	Driver
Dimmable article	Phase cut
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Type of light emission	Single emission
Net weight	1,924 Kg
Electrostatic discharge protection	No
Surge protection	No

Finishing casing	
Material	Iron
Colour	Embossed white RAL 9003
Processing	Coating

Finishing diffuser	
Material	PMMA
Colour	opaline

Box_W1 Mono Emission



Wall Lights | 220-240 V | 108 topLED 40 W DC - 41 W AC | CRI 80 | Base
8776

Single emission wall lights for indoor application. The warm white LED light source with a diffused light distribution is composed of 108 topLED LEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 4630 lm, with a 115.8 lm/W nominal luminous efficacy.

The device body is made of iron and features a embossed white ral 9003 finish, processed by means of coating; the diffuser is made of pmma. The ingress protection degree is IP40; the total weight is of 1,924 kg.

The total absorbed power is 41 W.

The device features protection class I and can be wall lights-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Energy efficiency class

This product contains 3 light sources of energy efficiency class E.

Illuminotechnical Features

Light Output Ratio (LOR)	73 %
Source lumens	4630 lm
Delivered lumens	3419 lm
Consumption	41 W
Luminaire efficacy	83 lm/W
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	80 Ra
Junction temperature (lighting fixture)	80

Standard Operating Ambient Temperature 25°C

LED Life / Failure Ratio


L70 B20 C0 72500h

UGR

UGR axial	17
UGR transversal	23.6
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL

C90/C270 optics	111°
C0/C180 optics	126°
Light distribution simmetry	Symmetrical 2 assis



Distance [m]	Cone diameter [m]	illuminance [lx]	E(0°)	E(C90)	E(C0)
0.5	1.46 1.98	4311 395 204	55.5°	63.2°	
1.0	2.91 3.96	1078 99 51	55.5°	63.2°	
1.5	4.37 5.94	479 44 23	55.5°	63.2°	
2.0	5.82 7.92	269 25 13	55.5°	63.2°	
2.5	7.28 9.90	172 16 8	55.5°	63.2°	
3.0	8.73 11.88	120 11 6	55.5°	63.2°	

Distance [m] Cone diameter [m] illuminance [lx]

— C0/C180 (Half-peak divergence: 126.4°)
- - C90/C270 (Half-peak divergence: 111.0°)

Box_W1 Mono Emission



Box_W1 Mono Emission | Wall Lights | Accessories
8776



Dimmer
220-240V

Code

KIT0026