


Ceiling Lights | 220-240 V
42 topLED 8 W DC - 10 W AC | CRI 85
7807



Technical data	
Construction year	2015
Type	Surface
Installation position	Wall lights - Ceiling
Installation environment	Indoor - Outdoor
Light Source	LED
Total Power	10 W
Source lumens	987 lm
Voltage	220 - 240 V AC
Frequency	50 - 60 Hz
CCT / Tone	3000 K
Colour rendering index	85 Ra
C.C. / C.V.	AC
Safety class	2
IP	IP65
IK	IK10
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	Driver
Dimmable article	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Type of light emission	Double emission
Net weight	0.875 Kg
Electrostatic discharge protection	No
Surge protection	No

Finishing diffuser	
Material	PE
Colour	neutral

Finishing mounting frame	
Material	PC
Colour	white

Ceiling Lights | 220-240 V | 42 topLED 8 W DC - 10 W AC | CRI 85 | Base 7807


Double emission ceiling lights for indoor or outdoor application. The warm white LED light source with a diffused light distribution is composed of 42 topLEDs with CCT of 3000 K and a CRI 85; the source luminous flux is 987 lm, with a 123.4 lm/W nominal luminous efficacy.

The diffuser is made of pe; the mounting frame is made of PC, with a white finish. The ingress protection degree is IP65; the total weight is of 0.875 kg.

The total absorbed power is 10 W.

The device features protection class II and can be wall lights or ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.



0.5	1.61 1.52	E(0°) E(C90) E(C0)	58.1° 58.1° 56.6°	669 49 56
1.0	3.21 3.03	E(0°) E(C90) E(C0)	58.1° 58.1° 56.6°	167 12 14
1.5	4.82 4.55	E(0°) E(C90) E(C0)	58.1° 58.1° 56.6°	74 5 6
2.0	6.43 6.07	E(0°) E(C90) E(C0)	58.1° 58.1° 56.6°	42 3 3
2.5	8.03 7.58	E(0°) E(C90) E(C0)	58.1° 58.1° 56.6°	27 2 2
3.0	9.64 9.10	E(0°) E(C90) E(C0)	58.1° 58.1° 56.6°	19 1 2

Distance [m]

Cone diameter [m]

Illuminance [lx]

C0/C180 (Half-peak divergence: 113.2°)

C90/C270 (Half-peak divergence: 116.2°)

Energy efficiency class

This product contains a light source of energy efficiency class F.

Illuminotechnical Features

Light Output Ratio (LOR)	70 %
Source lumens	987 lm
Delivered lumens	696 lm
Consumption	10 W
Luminaire efficacy	69 lm/W
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	85 Ra
Junction temperature (lighting fixture)	80

Standard Operating Ambient Temperature	-20 / +50°C
----------------------------------------	-------------

LED Life / Failure Ratio

L70 B20 C0 72500h

UGR

UGR axial	14.6
UGR transversal	14.4
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL

C0/C180 optics	113°
Light distribution simmetry	Symmetrical