Oh!_FL65 E27



Floor Lamp | 220-240 V | 1xE27 16150



Technical data	
Туре	Floor Lamp
Installation position	Floor
Installation environment	Outdoor
Lamp cap	1 x E27 Max 30W
Light emission direction	upward
Frequency	50-60 Hz
Optics	Diffused
Safety class	2
IP	IP65
IK	IK10
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Dimmable article	No
Directional	No

No

No

No

Yes

5 m

No 1.300 Kg

Type F





Finishing diffe	user				
Material	PE				
Colour	neutral				
Finishing mounting frame					
Material	PC				
Colour	white				

Tilting

Walk-over

Drive-over

Cable included

Electric socket

Cable length

Resin potting

Net weight

Oh!_FL65 E27



Floor Lamp | 220-240 V | 1xE27 | Base **16150**

Double emission floor lamp for outdoor application. Compatibility:, halogen 30 W; lamp cap 1xE27.

The diffuser is made of pe; the mounting frame is made of PC, with a white finish. The ingress protection degree is IP65; the total weight is of 1.300 kg.


. The power supply cable is included and features a 5 m length.

The device features protection class II and can be floor-mounted with an outer casing, code 14930(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.

Illuminotechnical Features		
Light Output Ratio (LOR)	79 %	
Source lumens	405 lm	
Delivered lumens	634 lm	
Consumption	14 W	
Luminaire efficacy	57 lm/W	
Colour temperature	2800 K	
Colour rendering index	100 Ra	
Junction temperature (lighting fixture)	80	
Standard Operating Ambient Temperature	-20 / +50°C	

OPTICAL	
C0/C180 optics	180°
Light distribution simmetry	Symmetrical



Oh!_FL65 E27



Oh!_FL65 E27 | Floor Lamp | Accessories 16150

	22	Outer casing - outer casing for installation on ground or on concrete	Code 14930
111	30 0 13 0 13 0 13 0 13 0 13 0 13 0 13 0	Pegs installation position: land,Cover material: pc	Code 14931
		Connector	Code 14992