

#### Floor Lamp | 220-240 V | 1xE27 16160



Technical data	
Туре	Floor Lamp
Installation position	Floor
Installation environment	Outdoor
Lamp cap	1 x E27 Max 46W
Light emission direction	upward
Frequency	50-60 Hz
Optics	Diffused
Safety class	2
IP	IP65
IK	IK10
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Dimmable article	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes





Finishing diffuser				
Material	PE			
Colour	neutral			
Finishing mou	ınting frame			
Material	PC			

white

Colour

Type F

5 m

No 2.000 Kg

Electric socket

Cable length

Resin potting

Net weight

### Oh!\_FL65 E27



## Floor Lamp | 220-240 V | 1xE27 | Base **16160**

Single emission floor lamp for outdoor application. Compatibility: LED lamp, halogen 46 W, compact fluo 20 W; lamp cap 1xE27.

The diffuser is made of pe; the mounting frame is made of PC, with a white finish. The ingress protection degree is IP65; the total weight is of 2.000 kg.


. The power supply cable is included and features a 5 m length.

The device features protection class II and can be floor-mounted with an outer casing, code 14930(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.

79 %	
700 lm	
975 lm	
20 W	
61 lm/W	
100 Ra	
80	
-20 / +50°C	

OPTICAL	
C0/C180 optics	180°
Light distribution simmetry	Symmetrical



# Oh!\_FL65 E27



#### Oh!\_FL65 E27 | Floor Lamp | Accessories 16160

O H	011	Outer casing - outer casing for installation on ground or on concrete	<b>Code</b> 14930
111	30 O 13	Pegs installation position: land,Cover material: pc	<b>Code</b> 14931
7 111 \$300	0 30	anti-theft - anti-theft ground fixing bracket	<b>Code</b> 14080
4 4 5	270	Tie rods	<b>Code</b> 53890
		Connector	<b>Code</b> 14992