


Floor Lamp | 220-240 V | 1xE27 16164



Technical data	
Installation position	Floor
Installation environment	Outdoor
Lamp cap	1 x E27 Max 57W
Light emission direction	upward
Frequency	50-60 Hz
Optics	Diffused
Safety class	2
IP	IP65
IK	IK10
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Dimmable article	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Electric socket	Type F
Cable length	5 m
Resin potting	No
Net weight	7.200 Kg





Finishing diffu	iser	
Material	PE	
Colour	neutral	
Finishing mou	Inting frame	

Finishing mounting frame		
Material	PC	
Colour	white	

Oh!_FL65 E27



Floor Lamp | 220-240 V | 1xE27 | Base 16164

Single emission floor lamp for outdoor application. Compatibility: LED lamp, halogen 57 W, compact fluo 30 W; lamp cap 1xE27.

The diffuser is made of pe; the mounting frame is made of PC, with a white finish. The ingress protection degree is IP65; the total weight is of 7.200 kg.


. The power supply cable is included and features a 5 m length.

The device features protection class II and can be floor-mounted with an outer casing, code 14930(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.

Illuminotechnical Features	
Light Output Ratio (LOR)	79 %
Source lumens	915 lm
Delivered lumens	1506 lm
Consumption	30 W
Luminaire efficacy	63 lm/W
Colour rendering index	100 Ra
Junction temperature (lighting fixture)	80
Standard Operating Ambient Temperature	-20 / +50°C

OPTICAL	
C0/C180 optics	180°
Light distribution simmetry	Symmetrical



Oh!_FL65 E27



Oh!_FL65 E27 | Floor Lamp | Accessories 16164

O HI	011	Outer casing - outer casing for installation on ground or on concrete	Code 14930
	50 V	Pegs - peg for ground mounting	Code 14937
7 111 \$000	0 36	anti-theft - anti-theft ground fixing bracket	Code 14082
W 4 4 5	270	Tie rods	Code 53890
		Connector	Code 14992