
Rose_P

Pendant Luminaires | 220-240 V | 3xE27 7657



Technical data		
Туре	Surface	
Installation position	Ceiling	
Installation environment	Indoor	
Lamp cap	3 x E27 Max 46W	
Light emission direction	downward	
Frequency	50-60 Hz	
Safety class	1	
IP	IP20	
Glow wire test	850°	
Direct mounting on normally flammable surfaces	Yes	
CE	Yes	
Dimmable article	No	
Directional	No	
Tilting	No	
Walk-over	No	
Drive-over	No	
Cable included	Yes	
Cable length	2.5 m	
Resin potting	No	
Net weight	6.410 Kg	

[Ħ < ↔ 🕅 🕅 🗘 🖉 ± 📼 🗋 ↔



Finishing casing			
Material	Iron		
Colour	Embossed white RAL 9003		
Processing	Coating		

r moning amaoor	
Material	PE
Colour	neutral

Rose_P

Pendant Luminaires | 220-240 V | 3xE27 | Base **7657**

Double emission pendant luminaires for indoor application. Compatibility: LED lamp, halogen 46 W, compact fluo 30 W; lamp cap 3xE27.

The device body is made of iron and features a embossed white ral 9003 finish, processed by means of coating; the diffuser is made of pe. The ingress protection degree is IP20; the total weight is of 6.410 kg.

. The power supply cable is included and features a 2.5 m length.

The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Illuminotechnical Features	
Light Output Ratio (LOR)	71 %
Source lumens	2100 lm
Delivered lumens	1502 lm
Consumption	138 W
Luminaire efficacy	15 lm/W
Colour temperature	2500 K
Colour rendering index	100 Ra
Junction temperature (lighting fixture)	80
Standard Operating Ambient Temperature	25°C

