


Ceiling Lights | 220-240 V | 4xE27





| Technical data | | |
|--|--------------------------|--|
| | | |
| Installation position | Wall lights - Ceiling | |
| Installation environment | Indoor | |
| Lamp cap | 4 x E27 Max 46W | |
| Light emission direction | downward | |
| Frequency | 50-60 Hz | |
| Safety class | 1 | |
| IP | IP20 | |
| Glow wire test | 850° | |
| Direct mounting on normally flammable surfaces | Yes | |
| CE | Yes | |
| Dimmable article | No | |
| Directional | No | |
| Tilting | No | |
| Walk-over | No | |
| Drive-over | No | |
| Cable included | No | |
| Resin potting | No | |





| Finishing casing Material Iron Colour black Processing Coating Finishing diffuser Material Glass | | | |
|---|------------------|---------|--|
| Colour black Processing Coating Finishing diffuser Material Glass | Finishing casing | 9 | |
| Processing Coating Finishing diffuser Material Glass | Material | Iron | |
| Finishing diffuser Material Glass | Colour | black | |
| Material Glass | Processing | Coating | |
| Material Glass | | | |
| | Finishing diffus | er | |
| | Material | Glass | |
| Colour white | Colour | white | |

| Finishing mounting frame | | | |
|--------------------------|----------------|--|--|
| Material | Iron | | |
| Colour | White RAL 9016 | | |
| Processing | Coating | | |

Sandblasting

Processing

7.600 Kg

Net weight

Zig Zag_S



Ceiling Lights | 220-240 V | 4xE27 **7289**

Single emission ceiling lights for indoor application. Compatibility: LED lamp, compact fluo 20 W, halogen 46 W; lamp cap 4xE27.

The device body is made of iron and features a black finish, processed by means of coating; the diffuser is made of glass with a sandblasting treatment; the mounting frame is made of iron, with a white ral 9016 finish, processed by means of coating. The ingress protection degree is IP20; the total weight is of 7.600 kg.

The device features protection class I and can be wall lights or ceilingmounted.

Compliant with the EN 60598-1 standard and its specific provisions.

| Illuminotechnical Features | |
|---|---------|
| Source lumens | 2800 lm |
| Colour temperature | 2500 K |
| Colour rendering index | 100 Ra |
| Junction temperature (lighting fixture) | 80 |
| | |
| Standard Operating Ambient Temperature | 25°C |
| | |