
Zig Zag_S

Ceiling Lights | 220-240 V | 2xE27 7401



Technical data		
Туре	Surface	
Installation position	Wall lights - Ceiling	
Installation environment	Indoor	
Lamp cap	2 x E27 Max 46W	
Light emission direction	downward	
Frequency	50-60 Hz	
Safety class	1	
IP	IP20	
Glow wire test	850°	
Direct mounting on normally flammable surfaces	Yes	
CE	Yes	
Dimmable article	No	
Directional	No	
Tilting	No	
Walk-over	No	
Drive-over	No	
Cable included	No	
Resin potting	No	
Net weight	2.633 Kg	

[Ħ < € 🕺 🕱 🕐 ± 🖂 ⊡



Finishing casin	9
Material	Aluminium
Processing	Anodisation
Finishing diffus	er
Material	Glass
Colour	white
Processing	Sandblasting
Finishing moun	ting frame
Material	Iron
Colour	White RAL 9016
Processing	Coating

Zig Zag_S

Ceiling Lights | 220-240 V | 2xE27 7401

Single emission ceiling lights for indoor application. Compatibility: LED lamp, halogen 46 W, compact fluo 20 W; lamp cap 2xE27.

The device body is made of aluminium, processed by means of anodisation; the diffuser is made of glass with a sandblasting treatment; the mounting frame is made of iron, with a white ral 9016 finish, processed by means of coating. The ingress protection degree is IP20; the total weight is of 2.633 kg.

The device features protection class I and can be wall lights or ceilingmounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Illuminotechnical Features		
Source lumens	1400 lm	
Colour temperature	2800 K	
Colour rendering index	100 Ra	
Junction temperature (lighting fixture)	80	
Standard Operating Ambient Temperature	25°C	