

Project
Type
Notes
Quantity
Date

GENERAL

Ceiling
Surface
Feel Jade
similar to NCS S 2005 - G90Y^a
IP20
Interior
835 lm

LED

3000 K
CRI ≥ 90
L80 / 50000 h
2-step binning

OPTICAL

Opal


ELECTRICAL

phase-cut dim
220 - 240 V
Total connected power 14.1 W
Class 1
Safety distance 0.3 m


PHYSICAL

Diameter 700 mm
Height 90 mm
2.1 kg

^a Color may deviate slightly due to production conditions.



Round shape ceiling surface mounted luminaire with diffuse light; aluminium base in White Matt wet painted; matt texture; steel diffuser; surface Feel Jade wet painted; matt texture; similar to NCS S 2005 - G90Y; white opal glass handblown; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; CRI (Colour Rendering Index) ≥ 90 ; degree of protection IP20; PC1; driver included; light source replaceable by an authorized professional; control gear replaceable by end-user;






WEVER & DUCRÉ
LIGHTING

CLEA 3.0

181384FJ5

LIGHT DISTRIBUTION



Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.96	0.92	0.88	0.85	0.81
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.