



WEVER & DUCRÉ
LIGHTING

CLEA WALL 2.0

181584B3

Project

Type

Notes

Quantity

Date

GENERAL

Wall

Surface

Black Matt

RAL 9011^a

IP20

Interior

615 lm

LED

2700 K

CRI ≥ 90

L80 / 50000 h

2-step binning

OPTICAL

Opal

ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 9.9 W

Class 1

Safety distance 0.3 m



PHYSICAL

Diameter 500 mm


Height 134 mm

1.3 kg

^a Color may deviate slightly due to production conditions.



Round shape wall surface mounted luminaire with diffuse light; aluminium base in White Matt wet painted; matt texture; steel diffuser; surface Black Matt wet painted; matt texture; RAL 9011; white opal glass handblown; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; CRI (Colour Rendering Index) ≥ 90 ; degree of protection IP20; PC1; driver included; light source replaceable by an authorized professional; control gear replaceable by end-user;






WEVER & DUCRÉ
LIGHTING

CLEA WALL 2.0

181584B3

LIGHT DISTRIBUTION



Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.96	0.92	0.88	0.85	0.81
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.