



WEVER & DUCRÉ  
LIGHTING

# FINLIN WALL 1.0

370584B5

Project

Type

Notes

Quantity

Date

## GENERAL

Wall  
Surface  
Black Matt  
RAL 9011<sup>a</sup>  
IP20  
Interior  
455 lm

## LED

3000 K  
CRI  $\geq$  90  
L80 / 60000 h  
3-step binning


## ELECTRICAL

phase-cut dim  
220 - 240 V  
Total connected power 5.1 W  
Class 1  
Safety distance 0.3 m


## PHYSICAL

Diameter 9 mm  
Height 623 mm  
0.1 kg


<sup>a</sup> Color may deviate slightly due to production conditions.



Wall surface luminaire made from aluminium; surface Black Matt; powder coated; matt texture; RAL 9011; opal PMMA diffuser; PCB 3-step binning; phase-cut dim; light colour 3000 K; binning initial MacAdam  $\leq$  3 SDCM; CRI  $\geq$  90; CRI (Colour Rendering Index)  $\geq$  90; 220 - 240 V; degree of protection IP20; PC1; driver included; light source replaceable by an authorized professional; control gear replaceable by end-user;



## LIGHT DISTRIBUTION





**WEVER & DUCRÉ**  
LIGHTING

# FINLIN WALL 1.0

370584B5

## Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.96	0.93	0.89	0.86	0.83
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF <sup>a</sup>	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF <sup>a</sup>	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## MOUNTING

### wall-/base-spacer

TYPE	L · W · H (MM)	ORDERCODE
FINLIN	45 · 27 · 38	9 0 0 1 9 5 B 0