


## FINLIN WALL 3.0

370784CH5

Project	
Туре	
Notes	
Quantity	
Date	

GENERAL
Wall
Surface
Black Matt + Champagne
IP20
Interior
760 lm
LED
3000 K
ELECTRICAL
phase-cut dim 220 - 240 V
phase-cut dim 220 - 240 V
phase-cut dim 220 - 240 V Total connected power 10.0 W Class 1
phase-cut dim 220 - 240 V Total connected power 10.0 W Class 1
phase-cut dim 220 - 240 V Total connected power 10.0 W
phase-cut dim 220 - 240 V Total connected power 10.0 W Class 1 Safety distance 0.3 m
phase-cut dim 220 - 240 V Total connected power 10.0 W Class 1 Safety distance 0.3 m  PHYSICAL Diameter 9 mm
phase-cut dim 220 - 240 V Total connected power 10.0 W Class 1 Safety distance 0.3 m





Wall surface luminaire made from aluminium; surface Black Matt + Champagne; powder coated; matt texture; opal PMMA diffuser; PCB 3-step binning; phase-cut dim; light colour 3000 K; CRI (Colour Rendering Index)  $\[Mathbb{N}\]$  90; 220 - 240 V; degree of protection IP20; PCI; driver included; light source replaceable by an authorized professional; control gear replaceable by end-user;



March 23, 2023



## FINLIN WALL 3.0

370784CH5

## **MOUNTING**

wall-/base-spacer

TYPE	L·W·H (MM)	ORDERCODE
FINLIN	45.27.38	900195B0