



WEVER & DUCRÉ  
LIGHTING

# GIGANT 10.0

213385W4

Project
Type
Notes
Quantity
Date

### GENERAL

Ceiling
Suspended
White LLDPE
IP20
Interior
5330 lm

### LED

3000 K
CRI ≥ 80
L80 / 60000 h
3-step binning

### OPTICAL


UGR < 19
∅65° < 3000 cd/m²

### ELECTRICAL


DALI dim
220 - 240 V
Total connected power 42 W
Class 1
Safety distance 0.3 m

### PHYSICAL


Diameter 1000 mm
Height 105 mm
8.8 kg



Ceiling suspended luminaire; surface White LLDPE; inclusive adjustable cable suspension max. 1500mm; PCB 3-step binning; DALI dim; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; 220 - 240 V; degree of protection IP20; PCI; light source replaceable by an authorized professional; control gear replaceable by end-user;



### LIGHT DISTRIBUTION



[213385W4] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.  
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



**WEVER & DUCRÉ**  
LIGHTING

# GIGANT 10.0

213385W4

## Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.96	0.93	0.89	0.85	0.82
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF <sup>a</sup>	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF <sup>a</sup>	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## SUSPENSION OPTIONS

### Suspension Set

TYPE	LENGTH (MM)	ORDERCODE
GIGANT   4.0m	4000	9 0 0 1 5 1 1 4