

TRACE WALL 1.0

333164H5

Project
Туре
Notes
Quantity
Date


GENERAL
Wall
Surface
Champagne + Black Matt
IP20
Interior
630 lm
LED
3000 K
2-step binning
ELECTRICAL
phase-cut dim
phase-cut dim 220 - 240 V
phase-cut dim 220 - 240 V
phase-cut dim 220 - 240 V Total connected power 8.0 W Class 1
phase-cut dim 220 - 240 V Total connected power 8.0 W Class 1
phase-cut dim 220 - 240 V Total connected power 8.0 W
phase-cut dim 220 - 240 V Total connected power 8.0 W Class 1 Safety distance 0.3 m PHYSICAL
phase-cut dim 220 - 240 V Total connected power 8.0 W Class 1 Safety distance 0.3 m PHYSICAL Length 70 mm
phase-cut dim 220 - 240 V Total connected power 8.0 W Class 1 Safety distance 0.3 m PHYSICAL Length 70 mm Width 80 mm
phase-cut dim 220 - 240 V Total connected power 8.0 W Class 1 Safety distance 0.3 m PHYSICAL













 $Wall \ surface \ luminaire \ made \ from \ aluminium; surface \ Champagne + Black \ Matt; up \ or \ down \ light \ emission;$ $with \ COB\ (Chip\ on\ Board)\ technology\ for\ maximum\ efficiency; phase-cut\ dim; light\ colour\ 3000\ K; binder and the colour\ bin$ $ning\ initial\ MacAdam \leq 2\ SDCM;\ 220\ -\ 240\ V;\ degree\ of\ protection\ IP20;\ PC1;\ driver\ included;\ light\ source$ $replaceable\ by\ an\ authorized\ professional;\ control\ gear\ replaceable\ by\ an\ authorized\ professional;$

