

Fabas Luce S.p.a. Via Luigi Talamoni 75, 20861 BRUGHERIO (MB) Italy Tel. +39 039 890691 Fax. +39 039 2142208

info@fabasluce.it - www.fabasluce.it - www.atiled.it








## Data sheet







## Yuma 2 - Ground recessed luminaire

Drive-over 2000 Kg spot light, 4 lights. Application with outer casing. Outer casing included. Frame made of AISI 316 stainless steel. Natural anodized finishing.

Color Lumen LED source LED characteristics Type of cooling LED efficiency LED mumber Operating ambient temperature CRI Optics Power supply Power supply Power pack type Total absorbed power IP IIK Class Dimensions H: 133 Ø: 70 mm. Box dimensions H: 150 W: 95 D: 95 mm. Hole diameter Net weight Optiver Driver Driver Driver Driver Included Designer Bar code  Power LED	Material	Stainless steel AISI 316
LED characteristics Type of cooling LED efficiency LED efficiency LED number Operating ambient temperature CRI Optics Diffused beam Power supply Power pack type Total absorbed power IP IP IP67 IK I0 Class Class I Dimensions H: 133 Ø: 70 mm. Box dimensions H: 150 W: 95 D: 95 mm. Hole diameter Net weight O,50 Kg. Gross weight Warranty type Driver Designer  Dimensions Dimensions Driver Included Designer  Power LED Passive Passive Cassi Diffused Designer -20°C +40°C -20°C +	Color	Stainless steel
Type of cooling LED efficiency LED number Operating ambient temperature CRI Optics Diffused beam Power supply Power pack type Total absorbed power IP IP IP67 IK I0 Class Class I Dimensions H: 133 Ø: 70 mm. Box dimensions H: 150 W: 95 D: 95 mm. Hole diameter Net weight Gross weight Warranty type Driver Designer  Dimensions Dimensions Driver Included Designer  Fassive Alle Mey85°C ClavC CP OPIM (A)  10 Class Class I Dimensions Class I Dimensions Dimensions Class I Dimensions Dimensions Class I Dimensions Class I Dimensions Dimensions Class I Dimensions Class I Dimensions Diver Driver Included Designer S.T. Fabas Luce	Lumen LED source	125lm
LED efficiency LED number  Operating ambient temperature  CRI Optics Optics Diffused beam Power supply Power pack type On/Off Total absorbed power IP IP IP67 IK I0 Class Class I Dimensions H: 133 Ø: 70 mm. Box dimensions H: 150 W: 95 D: 95 mm. Hole diameter Net weight O,50 Kg. Gross weight Warranty type Driver Designer  Driver Included Designer  -20°C +40°C -20°C -20°C +40°C	LED characteristics	Power LED
LED number  Operating ambient temperature  CRI  Optics  Diffused beam  Power supply  Power pack type  Total absorbed power  IP  IP  IP67  IK  Class  Class I  Dimensions  H: 133 Ø: 70 mm.  Box dimensions  H: 150 W: 95 D: 95 mm.  Net weight  O,50 Kg.  Gross weight  Warranty type  Driver  Designer  Laso  Diffused beam  Pon/Off  Con/Off  Con/Off  Con/Off  Total absorbed power  Diffused beam  Pon/Off  Pon/Off  Diffused beam  Pon/Off  Pon/Off  Diffused beam  Pon/Off  Pon/Off  Diffused beam  Pon/Off  Doilor  Doilor  Pon/Off  Diffused beam  Pon/Off  Doilor  Do	Type of cooling	Passive
Operating ambient temperature  CRI  Optics  Diffused beam  Power supply  220-240V AC  Power pack type  Total absorbed power  IP  IP  IP67  IK  Class  Class I  Dimensions  H: 133 Ø: 70 mm.  Box dimensions  H: 150 W: 95 D: 95 mm.  Net weight  O,50 Kg.  Gross weight  Varranty type  Warranty B  Driver  Designer  -20°C +40°C  -20°C  -20°C +40°C  -20°C  -20°C +40°C  -20°C  -20°  -2	LED efficiency	69lm/w@85°C
CRI >80 Optics Diffused beam Power supply 220-240V AC Power pack type On/Off Total absorbed power 2.8W IP IP67 IK 10 Class Class I Dimensions H: 133 Ø: 70 mm. Box dimensions H: 150 W: 95 D: 95 mm. Hole diameter 95 mm. Net weight 0,50 Kg. Gross weight 0,60 Kg. Warranty type Warranty B Driver Driver Included Designer S.T. Fabas Luce	LED number	1
Optics Diffused beam Power supply 220-240V AC Power pack type On/Off Total absorbed power 2.8W IP IP67 IK 10 Class Class I Dimensions H: 133 Ø: 70 mm. Box dimensions H: 150 W: 95 D: 95 mm. Hole diameter 95 mm. Net weight 0,50 Kg. Gross weight 0,60 Kg. Warranty type Warranty B Driver Driver Included Designer S.T. Fabas Luce	Operating ambient temperature	-20°C +40°C
Power supply Power pack type On/Off Total absorbed power IP IR Class Class I Dimensions H: 133 Ø: 70 mm. Box dimensions H: 150 W: 95 D: 95 mm. Hole diameter Net weight Gross weight O,60 Kg. Warranty type Warranty B Driver Designer S.T. Fabas Luce	CRI	>80
Power pack type Total absorbed power  IP IP67 IK I0 Class Class I Dimensions H: 133 Ø: 70 mm. Box dimensions H: 150 W: 95 D: 95 mm. Hole diameter Net weight Gross weight Varranty type Driver Designer On/Off  On/Off  On/Off  On/Off  On/Off  On/Off  On/Off  On/Off  IP67  IK I0 On/Off  On/Off  IP67  IK I0 On/Off  On/Off  On/Off  IP67  IV In On/Off  On/Off  On/Off  IP67  IV In On/Off  On/Off  IP67  IV In On On On In On On On In On	Optics	Diffused beam
Total absorbed power IP IP IP67 IK 10 Class Class I Dimensions H: 133 Ø: 70 mm. Box dimensions H: 150 W: 95 D: 95 mm. Hole diameter 95 mm. Net weight 0,50 Kg. Gross weight Warranty type Warranty B Driver Designer  2.8W IP67 IP67 IP67 IP67 IP67 IP67 IP67 IP67		220-240V AC
IP IP67 IK 10 Class Class I Dimensions H: 133 Ø: 70 mm. Box dimensions H: 150 W: 95 D: 95 mm. Hole diameter 95 mm. Net weight 0,50 Kg. Gross weight 0,60 Kg. Warranty type Warranty B Driver Driver Included Designer S.T. Fabas Luce		On/Off
IK Class Class I Dimensions H: 133 Ø: 70 mm.  Box dimensions H: 150 W: 95 D: 95 mm.  Hole diameter 95 mm.  Net weight 0,50 Kg.  Gross weight 0,60 Kg.  Warranty type Warranty B Driver Driver Driver Included Designer S.T. Fabas Luce	Total absorbed power	2.8W
Class I Dimensions H: 133 Ø: 70 mm. Box dimensions H: 150 W: 95 D: 95 mm. Hole diameter 95 mm. Net weight 0,50 Kg. Gross weight 0,60 Kg. Warranty type Warranty B Driver Driver Included Designer S.T. Fabas Luce	IP	IP67
Dimensions Box dimensions H: 133 Ø: 70 mm. Box dimensions H: 150 W: 95 D: 95 mm. Hole diameter 95 mm. Net weight 0,50 Kg. Gross weight 0,60 Kg. Warranty type Warranty B Driver Driver Driver Included Designer S.T. Fabas Luce	IK	10
Box dimensions H: 150 W: 95 D: 95 mm.  Hole diameter 95 mm.  Net weight 0,50 Kg.  Gross weight 0,60 Kg.  Warranty type Warranty B  Driver Driver Designer S.T. Fabas Luce	Class	Class I
Hole diameter 95 mm.  Net weight 0,50 Kg.  Gross weight 0,60 Kg.  Warranty type Warranty B  Driver Driver Included  Designer S.T. Fabas Luce	Dimensions	H: 133 Ø: 70 mm.
Net weight Gross weight O,60 Kg. Warranty type Warranty B Driver Driver Included Designer S.T. Fabas Luce	Box dimensions	H: 150 W: 95 D: 95 mm.
Gross weight  Warranty type  Driver  Designer  O,60 Kg.  Warranty B  Driver Included  S.T. Fabas Luce		95 mm.
Warranty type  Driver  Designer  Warranty B  Driver Included  S.T. Fabas Luce		0,50 Kg.
Driver Driver Included Designer S.T. Fabas Luce	Gross weight	0,60 Kg.
Designer S.T. Fabas Luce	Warranty type	-
	Driver	Driver Included
Bar code <b>8019282009894</b>	_	
	Bar code	8019282009894

## **Warm white**



**6910-02-024** 8019282009894

